



**R10** 

IP67

WARNING LIGHTING DIRECTIONAL LIGHTING LIGHTBARS WHITE LIGHTING REVERSING SAFETY



## DIRECTIONALS

## ED9040 SERIES R65 Class I & II Hide-A-LED

The ED9040 Hide-A-LED Series provides the functionality of a warning light in a low profile design, allowing the vehicles safe arrival to the scene. R65 Class II & Class I light output. Synchronisation capability, and a choice of 29\* flash patterns for single-colour and 69\* flash patterns for dual colour allow the creation of an attention-getting, multi-colour warning system with half the number of lights typically required. The ED9040 offers flexibility with multiple flush mounting applications on virtually any surface including bumpers and on sides of vehicles.

## **Models** AMPS PART NO. COLOUR MOUNT VDC . 34mm (1.3") Surface / Flush (1" Hole) ED9040X 1.2 12-24 ED9040XX 12-24 0.6 Surface / Flush (1" Hole) 34mm Replace X in part number with desired LED colour: A = amber, G = green (1.3'')ø25mm (0.99") GASKET MOUNTING **Features and Benefits** Slim low-profile design with 6 powerful LEDs for a bright warning light 37mm (1.4") All-in-module: all controls imbedded in the head light, avoiding a LED flash controller Optimised lens and optical system, maximising light beam inmultiple single or dual • colour variations Discreet flush mount, virtually applicable on any vehicle surface - insertable in a 1" hole, • with 10" pigtail cable Steady burn override for worklight functionality • Syncable with compatible ECCO directionals: ED3700, ED3701/ED3702, ED3706/ED3712, • 267±13mm 10 50+0 50" ED3766, and ED3777/ED3779 Series • Temperature Range: -30°C to + 50°C (-22°F to +122°F)

\* Not all flash patterns are R65 approved patterns, please refer to installation manual for the list of patterns that are approved to R65.

+44 (0)113 237 5340 | sales@eccogroup.com

Part of ECCO SAFETY GROUP™

JK

|ㅋㅋㅋㅋㅋㅋㅋㅋㅋ